



TES 80 Series *SmartCharge*

We designed the TES 80 Series EV Charging Station for commercial applications where drivers are likely to pay with a credit card. With our built-in credit card reader, drivers don't need a network membership to charge their vehicle. This is perfect for all commercial applications, including shopping malls, hospitals, municipal parking, and any retail location.

- 
- Two EV charging plugs / supports two parking spots
 - Easily implement desired pricing policy: Duration-based (hourly), Time-of-Use, and kWh
 - Credit card reader accepts all major credit cards
 - Supports physical and contactless payment options
 - Create access policies for public, private, or multi-group
 - Sharing features include:
 - Real-time availability
 - Station wait list feature
 - Alerts / notifications
 - Charging status
 - Smart card authentication
 - Pay with PlugShare
 - Large display delivers instructions, rates, and details
 - Video camera for future applications (e.g. vandalism, theft)
 - Optional cable management system

PAYMENTS ACCEPTED





TERRA

ENERGY SERVICES BY **ACDI**

Power Specs

AC Power Output, maximum (per port)	Level II: 7.2kW (240VAC@30A)
AC Power Input (per port)	Level II: 30A; Line 1, Line 2 and GND (no neutral)
Ports Per Charging Station	Two
Vehicle to Charger Connection (per port)	SAE J1772 EV Connector, 18ft Cable
Energy Metering Accuracy	+/-1%
Standby Power	6.5W typical
Service Panel Breaker (per port)	Dual-pole trip 40A breaker, dedicated circuit

Safety Specs

Safety, Ground Fault Circuit Interrupt	20mA CCID with auto retry (every 15 seconds)
Automatic Plug-Out Detection	Pwr terminated per SAE J1772 spec: SMS/email
General Safety Compliance	UL 2231-1, 2231-2, UL2594 and NEC Article 625

Network Specs

Data Communication Cellular	Cellular 4G LTE
Network Communication Protocol	OCPP
Network Security	HTTPS-WSS; 128 bit AES Encryption

Communication Device Specs

LED Array	High visibility, multi-color visual status indication
Display	Color LCD, 480 x 272
Operating Temperature	30 degree C to +50 degree C ambient

Environmental Specs

Outdoor Rated	NEMA 3R
Operating Humidity	Up to 95% non-condensing
Operating Temperature	30 degree C to +50 degree C ambient

Other Specs

Surge Protection	6kV@3,000A
EMI Compliance	FCC Part 15 Class A
Dimensions	11" H x 7.5" W x 7.5" D
Approximate Shipping Weights	Head Unit & Cable - 28 lbs. Pedestal Mount - 11 lbs. Wall Mount - 10 lbs.
Installation	Indoor / Outdoor
Wall and Cable Mount	Integrated

For more information on Terra Energy Services and our products, please call 800.990.2234 or visit terraenergyservice.com

